



UV-105 F4.5



UV to Extended Red 105mm F4.5 Nikon

- Chromatically corrected from 220nm to 900nm.
- Forensics, combustion, electric discharge.
- > 70% transmission from 220nm to 900nm.
- Macro (2:1) capability.



SPECIFICATION

| | |
|--------------------------|---|
| Part Number | PF10545MF-UV |
| Focal Length | 105mm |
| Construction | 6 elements in 6 groups |
| Maximum Aperture Ratio | 4.5 |
| Benchmark Wavelength | 587.56nm |
| Corrected Wavelength | 220nm ~ 900nm |
| Magnification | ∞ ~ 0.5 times |
| Image Size | \varnothing 43.6mm |
| Object Diameter (at 2:1) | \varnothing 87.2mm |
| Picture Angle | 23° 20' |
| Focussing Scale | ∞ ~ 0.48m (1.57 feet) |
| Magnification Scale | 1:10 ~ 1:2 |
| Aperture Stops | 4.5, 5.6, 8, 11, 16, 22, 32 |
| Object to Image Distance | ∞ ~ 428.6mm |
| Working Distance | ∞ ~ 274.1mm |
| Mount | Nikon F Mount. |
| Flange Focal Distance | 46.5mm (Standard F-mount) |
| Filter Size | M52 x 0.75 |
| Dimensions | \varnothing 68.5 x 116.5mm (108mm when at ∞ to flange) |
| Weight | 515g |